

## Single Row 7200B(d 10-130mm)

Nº do rolamento	Dimensões do limite (mm)			Classificações básicas de carga (kN)		Limiting speed(rpm )		Mass Kg
	d	D	B	Dynamic(Cr)	Static(Cor)	Grease	Oil	
7200B	10	30	9	5.3	2.7	19000	27000	0.03
7201B	12	32	10	6.9	3.2	18000	24000	0.036
7202B	15	35	11	7.9	4.2	16000	22000	0.045
7203B	17	40	12	9.9	5.5	14000	19000	0.065
7204B	20	47	14	13.4	7.6	12000	16000	0.11
7205B	25	52	15	14.8	9.3	10000	14000	0.13
7206B	30	62	16	20.5	13.5	8500	12000	0.2
7207B	35	72	17	28.3	14.8	7500	10000	0.28
7208B	40	80	18	34.5	23.8	6700	9000	0.42
7209B	45	85	19	34	24.6	6300	8500	0.42
7210B	50	90	20	40.4	25.6	5600	8000	0.47
7211B	55	100	21	46.3	36	5300	7000	0.62
7212B	60	110	22	56.1	44.3	4800	6300	0.8
7213B	65	120	23	65.7	50.2	4300	6000	1
7214B	70	125	24	70.4	56.3	4000	5600	1.1
7215B	75	130	25	68.6	58.2	3800	5300	1.2
7216B	80	140	26	78.7	65.7	4000	5300	1.45
7217B	85	150	28	83.2	74.1	3600	5000	1.85
7218B	90	160	30	107.6	92.4	3200	4300	2.3
7219B	95	170	32	121.4	106.7	3000	4000	2.7
7220B	100	180	34	140.7	102.5	2800	3800	3.3
7221B	105	190	36	143.3	128.5	2800	3800	3.55
7222B	110	200	38	153.8	144.3	2400	3400	4.35
7224B	120	215	40	165.4	161.4	2200	3200	5.2
7226B	130	230	40	170.8	174.2	1800	2800	6.05